



RFID READERS

Leader Race Reader

For effective reading of NLIS devices, ear tags and rumen pellets



FEATURES AND BENEFITS

- Compatible with all major scales and software
- Built especially for the livestock industry
- Use in all weather conditions
- User friendly LeaderLink NLIS transfer software
- Distinctive tones and very bright LED's identifying a device read, stores or non-functioning.
- Will not duplicate animal ID in current session
- Visual screen displays animal count
- Up to 1,000 sessions with max of up to 2,000 per session
- Up to 10,000 RFID storage
- Ability to clear the memory from the reader
- Reads and stores RFID number for easy download at a later time.
- Sends RFID number direct to scale indicator, laptop or PDA.
- Seven days a week helpline to original purchaser for first 12 months (conditions apply)
- Comes with Free NLIS Transfer Software – Leader Datalink

SPECIFICATIONS

- Requires external power supply 12volt (optional extra)
- Data Security: Non-volatile memory ensures all stored.
- RFID's are safe even if battery goes flat.
- Operating temperature: -10°C to + 60°C
- Operating frequency: 134.2 kHz HDX (half duplex)
- Read Distance: Up to 1200mm from antenna
- Read Speed: 100 Milliseconds
- Data Lead: 5m reader to computer serial lead
- Data Interface: Serial RS232 or Bluetooth (optional)
- Baud rate 9600, Data bits 8, No parity, stop bit 1

The reader component is able to be removed from the main panel; this enables the convenience of downloading information in your office without the need to bring the antenna along

