

# LEADER TAIL PAINT ORANGE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 29-Jan-2013

9317SP(cs)

CHEMWATCH 4799-61

Version No:2.1.1.1

CD 2012/4 Page 1 of 8

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NAME

LEADER TAIL PAINT ORANGE

### SYNONYMS

18023306

### PROPER SHIPPING NAME

AEROSOLS

### PRODUCT USE

■ Application is by spray atomisation from a hand held aerosol pack.  
Used according to manufacturer's directions.

### SUPPLIER

Company: Dy- Mark Pty Ltd

Address:

89 Formation Street

Wacol

QLD, 4076

Australia

Telephone: +61 7 3271 2222

Emergency Tel: +61 403 186 708

Fax: +61 7 3271 2751


Email: info@dymark.com.au

## Section 2 - HAZARDS IDENTIFICATION

### STATEMENT OF HAZARDOUS NATURE

**HAZARDOUS SUBSTANCE. DANGEROUS GOODS.** According to the Criteria of NOHSC, and the ADG Code.

### CHEMWATCH HAZARD RATINGS



### RISK

Risk Codes

R12

R38

R44

R50/53

R67

Risk Phrases

• Extremely flammable.

• Irritating to skin.

• Risk of explosion if heated under confinement.

• Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

• Vapours may cause drowsiness and dizziness.

### SAFETY

Safety Codes

S16

S24

S37

S29

S401

S35

S46

S57

Safety Phrases

• Keep away from sources of ignition. No smoking.

• Avoid contact with skin.

• Wear suitable gloves.

• Do not empty into drains.

• To clean the floor and all objects contaminated by this material, use water and detergent.

• This material and its container must be disposed of in a safe way.

• If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).

• Use appropriate container to avoid environmental contamination.

continued...

# LEADER TAIL PAINT ORANGE

## Chemwatch Independent Material Safety Data Sheet

Issue Date: 29-Jan-2013

9317SP(cs)

CHEMWATCH 4799-61

Version No:2.1.1.1

CD 2012/4 Page 2 of 8

### Section 2 - HAZARDS IDENTIFICATION

- S61
- Avoid release to the environment. Refer to special instructions/Safety data sheets.
- S60
- This material and its container must be disposed of as hazardous waste.

### Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
heptane	142-82-5	10-30
resin		1-15
filler		1-10
pigments		1-10
hydrocarbon propellant	68476-85-7.	20-50

### Section 4 - FIRST AID MEASURES

#### SWALLOWED

- - Avoid giving milk or oils.
  - Avoid giving alcohol.
- Not considered a normal route of entry.

#### EYE

- If aerosols come in contact with the eyes:
  - Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.
  - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
  - Transport to hospital or doctor without delay.
  - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

#### SKIN

- If solids or aerosol mists are deposited upon the skin:
  - Flush skin and hair with running water (and soap if available).
  - Remove any adhering solids with industrial skin cleansing cream.
  - DO NOT use solvents.
  - Seek medical attention in the event of irritation.

#### INHALED

- If aerosols, fumes or combustion products are inhaled:
  - Remove to fresh air.
  - Lay patient down. Keep warm and rested.
  - Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
  - If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

#### NOTES TO PHYSICIAN

- For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:
    - Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
    - Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> 50 mm Hg) should be intubated.
    - Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
    - A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Treat symptomatically.

### Section 5 - FIRE FIGHTING MEASURES

#### EXTINGUISHING MEDIA

- SMALL FIRE:
  - Water spray, dry chemical or CO<sub>2</sub>
- LARGE FIRE:
  - Water spray or fog.

continued...

# LEADER TAIL PAINT ORANGE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 29-Jan-2013

9317SP(cs)

CHEMWATCH 4799-61

Version No:2.1.1.1

CD 2012/4 Page 3 of 8

Section 5 - FIRE FIGHTING MEASURES

---

## FIRE FIGHTING

- - Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.

## FIRE/EXPLOSION HAZARD

- - Liquid and vapour are highly flammable.
- Severe fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Severe explosion hazard, in the form of vapour, when exposed to flame or spark.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>), other pyrolysis products typical of burning organic material.

Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

## FIRE INCOMPATIBILITY

- - Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

## HAZCHEM

2YE

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

### MINOR SPILLS

- - Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear protective clothing, impervious gloves and safety glasses.
- Shut off all possible sources of ignition and increase ventilation.

### MAJOR SPILLS

- - Remove leaking cylinders to a safe place if possible.
- Release pressure under safe, controlled conditions by opening the valve.
- DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.
- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

---

## Section 7 - HANDLING AND STORAGE

---

### PROCEDURE FOR HANDLING

- - DO NOT allow clothing wet with material to stay in contact with skin.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

### SUITABLE CONTAINER

- - Aerosol dispenser.
- Check that containers are clearly labelled.

### STORAGE INCOMPATIBILITY

- - Avoid reaction with oxidising agents.

### STORAGE REQUIREMENTS

- - Store below 38 deg. C.
- Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can.
- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.

continued...

# LEADER TAIL PAINT ORANGE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 29-Jan-2013

9317SP(cs)

CHEMWATCH 4799-61

Version No:2.1.1.1

CD 2012/4 Page 4 of 8

Section 7 - HANDLING AND STORAGE

- Keep containers securely sealed. Contents under pressure.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

#### MATERIAL DATA

HYDROCARBON PROPELLANT:

LEADER TAIL PAINT ORANGE:

- For butane:

Odour Threshold Value: 2591 ppm (recognition)

Butane in common with other homologues in the straight chain saturated aliphatic hydrocarbon series is not characterised by its toxicity but by its narcosis-inducing effects at high concentrations. The TLV is based on analogy with pentane by comparing their lower explosive limits in air.

Odour Safety Factor(OSF)

OSF=0.22 (n-BUTANE).

HEPTANE:

LEADER TAIL PAINT ORANGE:

- for heptane (all isomers)

The TLV-TWA is protective against narcotic and irritant effects which are greater than those of pentane or n-hexane but less than those of octane. The TLV-TWA applies to all isomers.<</>.

LEADER TAIL PAINT ORANGE:

- For liquefied petroleum gases (LPG):

TLV TWA: 1000 ppm, 1800 mg/m<sup>3</sup> (as LPG)

ES TWA: 1000 ppm, 1800 mg/m<sup>3</sup> (as LPG)

OES TWA: 1000 ppm, 1750 mg/m<sup>3</sup>; STEL: 1250 ppm, 2180 mg/m<sup>3</sup> (as LPG)

IDLH Level: 2000 ppm (lower explosive limit)

No chronic systemic effects have been reported from occupational exposure to LPG. The TLV-TWA is based on good hygiene practices and is thought to minimise the risk of fire or explosion.

Odour Safety Factor(OSF)

OSF=0.16 (hydrocarbon propellant).

Animals exposed by inhalation to 10 mg/m<sup>3</sup> titanium dioxide show no significant fibrosis, possibly reversible tissue reaction.

The architecture of lung air spaces remains intact.

HYDROCARBON PROPELLANT:

- For propane

Odour Safety Factor(OSF)

OSF=0.16 (PROPANE).

### PERSONAL PROTECTION

#### RESPIRATOR

•Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

#### EYE

■ No special equipment for minor exposure i.e. when handling small quantities.

OTHERWISE: For potentially moderate or heavy exposures:

- Safety glasses with side shields.

- NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.

#### HANDS/FEET

■ - No special equipment needed when handling small quantities.

- OTHERWISE:

- For potentially moderate exposures:

- Wear general protective gloves, eg. light weight rubber gloves.

#### OTHER

■ No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.

- Skin cleansing cream.

- Eyewash unit.

- Do not spray on hot surfaces.

- The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials

continued...

# LEADER TAIL PAINT ORANGE

## Chemwatch Independent Material Safety Data Sheet

Issue Date: 29-Jan-2013

9317SP(cs)

CHEMWATCH 4799-61

Version No:2.1.1.1

CD 2012/4 Page 5 of 8

### Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

including cotton.

- Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost.

BRETHERRICK: Handbook of Reactive Chemical Hazards.

#### ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

### Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

#### APPEARANCE

■ Supplied as an aerosol pack. Contents under PRESSURE.

Orange flammable liquid with a solvent odour; not miscible with water.

#### PHYSICAL PROPERTIES

Liquid.

Gas.

Does not mix with water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Immiscible
Flash Point (°C)	- 81 (propellant)	pH (1% solution)	Not Available
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Available
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	Not Available
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

### Section 10 - STABILITY AND REACTIVITY

#### CONDITIONS CONTRIBUTING TO INSTABILITY

■ - Elevated temperatures.

- Presence of open flame.

- Product is considered stable.

- Hazardous polymerisation will not occur.

*For incompatible materials - refer to Section 7 - Handling and Storage.*

### Section 11 - TOXICOLOGICAL INFORMATION

#### POTENTIAL HEALTH EFFECTS

##### ACUTE HEALTH EFFECTS

##### SWALLOWED

■ Accidental ingestion of the material may be damaging to the health of the individual.

Not normally a hazard due to physical form of product.

Considered an unlikely route of entry in commercial/industrial environments.

Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733).

##### EYE

■ There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

Not considered to be a risk because of the extreme volatility of the gas.

##### SKIN

■ This material can cause inflammation of the skin on contact in some persons.

The material may accentuate any pre-existing dermatitis condition.

continued...

# LEADER TAIL PAINT ORANGE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 29-Jan-2013

9317SP(cs)

CHEMWATCH 4799-61

Version No:2.1.1.1

CD 2012/4 Page 6 of 8

## Section 11 - TOXICOLOGICAL INFORMATION

Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

Spray mist may produce discomfort.

Open cuts, abraded or irritated skin should not be exposed to this material.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

### INHALED

■ Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.

Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Inhalation of toxic gases may cause:

- Central Nervous System effects including depression, headache, confusion, dizziness, stupor, coma and seizures;
- respiratory: acute lung swellings, shortness of breath, wheezing, rapid breathing, other symptoms and respiratory arrest;
- heart: collapse, irregular heartbeats and cardiac arrest;
- gastrointestinal: irritation, ulcers, nausea and vomiting (may be bloody), and abdominal pain.

Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.

Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.

Inhalation, by humans, of 1000 ppm heptane for 6 minutes was associated with slight dizziness; inhalation of higher concentrations for shorter periods, resulted in marked vertigo, incoordination, and hilarity. Signs of central nervous system (CNS) involvement occurred in the absence of noticeable mucous membrane irritation and were noticed promptly on entering such atmospheres.

Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour displace and replace air in breathing zone, acting as a simple asphyxiant.

WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.

### CHRONIC HEALTH EFFECTS

■ Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Principal route of occupational exposure to the gas is by inhalation.

Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS].

Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin. Chronic exposure to lighter hydrocarbons can cause nerve damage, peripheral neuropathy, bone marrow dysfunction and psychiatric disorders as well as damage the liver and kidneys.

There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

### TOXICITY AND IRRITATION

■ No significant acute toxicological data identified in literature search.  
inhalation of the gas.

## Section 12 - ECOLOGICAL INFORMATION

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This material and its container must be disposed of as hazardous waste.

Avoid release to the environment.

Refer to special instructions/ safety data sheets.

### Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
heptane	LOW	No Data Available	HIGH	MED
hydrocarbon propellant	No Data Available	No Data Available	No Data Available	No Data Available

continued...

# LEADER TAIL PAINT ORANGE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 29-Jan-2013

9317SP(cs)

CHEMWATCH 4799-61

Version No:2.1.1.1

CD 2012/4 Page 7 of 8

## Section 13 - DISPOSAL CONSIDERATIONS

■ Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction.
- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- Allow small quantities to evaporate.
- DO NOT incinerate or puncture aerosol cans.

## Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE GAS

### HAZCHEM:

2YE (ADG7)

### ADG7:

Class or Division	2.1	Subsidiary Risk:	None
UN No.:	1950	Packing Group:	None
Special Provision:	63 190 277 327	Limited Quantity:	See SP 277
Portable Tanks & Bulk Containers - Instruction:	None	Portable Tanks & Bulk Containers - Special Provision:	None
Packagings & IBCs - Packing Instruction:	P003 LP02	Packagings & IBCs - Special Packing Provision:	PP17 PP87 L2

Name and Description: AEROSOLS

### Land Transport UNDG:

Class or division	2.1	Subsidiary risk:	None
UN No.:	1950	UN packing group:	None
Shipping Name:	AEROSOLS		

### Air Transport IATA:

ICAO/IATA Class	2.1	ICAO/IATA Subrisk:	None
UN/ID Number:	1950	Packing Group:	-
Special provisions:	A145		
Cargo Only			
Packing Instructions:	203	Maximum Qty/Pack:	150 kg
Passenger and Cargo		Passenger and Cargo	
Packing Instructions:	203	Maximum Qty/Pack:	75 kg
Passenger and Cargo		Passenger and Cargo	
Limited Quantity		Limited Quantity	
Packing Instructions:	Y203	Maximum Qty/Pack:	30 kg G

Shipping name:AEROSOLS

### Maritime Transport IMDG:

IMDG Class	2.1	IMDG Subrisk:	SP63
UN Number:	1950	Packing Group:	None
EMS Number:	F- D, S- U	Special provisions:	63 190 277 327 344 959
Limited Quantities:	See SP277	Marine Pollutant:	Yes
Shipping name:	AEROSOLS		

continued...

# LEADER TAIL PAINT ORANGE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 29-Jan-2013

9317SP(cs)

CHEMWATCH 4799-61

Version No:2.1.1.1

CD 2012/4 Page 8 of 8

---

## Section 15 - REGULATORY INFORMATION

---

### Indications of Danger:

F+	Extremely flammable
N	Dangerous for the environment
Xi	Irritant

POISONS SCHEDULE None

### REGULATIONS

Regulations for ingredients

---

## Section 16 - OTHER INFORMATION

---

### INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
heptane	142- 82- 5, 31394- 54- 4
hydrocarbon propellant	68476- 85- 7, 68476- 86- 8

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references).

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 29-Jan-2013

Print Date: 29-Jan-2013

*This is the end of the MSDS.*